

PRODUCT DATA SHEET

IDEMITSU SN A5/B5 C2 5W-30 FULLY SYNTHETIC Power & Protection



Description

Idemitsu SN A5/B5 C2 5W-30 is a Full-Synthetic engine oil specially designed and formulated to provide superb driving pleasure along with improved fuel efficiency performance. An excellent choice for ensuring performance, efficiency & fuel economy.

Application

Recommended for all high performance modern Cars where SAE 5W-30 viscosity is recommended by OEM.

Characteristics

- Fully Synthetic engine oil
- Improved fuel economy
- Excellent start-up performance in low temperature and great durability at high temperature
- Minimize friction to optimize engine's performance
- Provides more stringent sludge control for piston and other engine parts, consequently keeping engine clean for longer engine life
- Provides superb protection against wear and corrosion
- Meets the requirements of API SN, ACEA A5/B5 C2

Typical Characteristics

ITEM	ASTM METHOD	IDEMITSU SN A5/B5 C2 5W-30 FULLY SYNTHETIC (Typical Value)
Viscosity Grade		SAE 5W-30
Color	D-1500	L2.5
Density 15 °C g/cm ³	D-4052	0.8530
Flash Point (COC) °C	D-92	228
Viscosity, cSt	@ 40 °C	63.05
	@ 100 °C	10.76
Viscosity Index	D-2270	162
Acid Number (mgKOH/g)	D-664	2.17
TBN HClO ₄ (mgKOH/g)	D-2896	8.11
Foaming @ 93.5°C (ml)	D-892	40-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.